

Introducing the Specifications of the Metro Ethernet Forum

MEF 20: User Network Interface Type 2 With Testing Support via MEF 21 & MEF 24

Approved MEF Specifications

MEf

•	MEF 2	Requirements and Framework for Ethernet Service Protection
•	MEF 3	Circuit Emulation Service Definitions, Framework and Requirements in Metro Ethernet Networks
•	MEF 4	Metro Ethernet Network Architecture Framework Part 1: Generic Framework
•	MEF 6.1	Metro Ethernet Services Definitions Phase 2
•	MEF 7	EMS-NMS Information Model
•	MEF 8	Implementation Agreement for the Emulation of PDH Circuits over Metro Ethernet Networks
•	MEF 9	Abstract Test Suite for Ethernet Services at the UNI
•	MEF 10.1	Ethernet Services Attributes Phase 2*
•	MEF 11	User Network Interface (UNI) Requirements and Framework
•	MEF 12	Metro Ethernet Network Architecture Framework Part 2: Ethernet Services Layer
•	MEF 13	User Network Interface (UNI) Type 1 Implementation Agreement
•	MEF 14	Abstract Test Suite for Traffic Management Phase 1
•	MEF 15	Requirements for Management of Metro Ethernet Phase 1 Network Elements
•	MEF 16	Ethernet Local Management Interface
•	MEF 17	Service OAM Framework and Requirements
•	MEF 18	Abstract Test Suite for Circuit Emulation Services
•	MEF 19	Abstract Test Suite for UNI Type 1
•	MEF 20	User Network Interface (UNI) Type 2 Implementation Agreement
•	MEF 21	Abstract Test Suite for UNI Type 2 Part 1: Link OAM
•	MEF 22	Mobile Backhaul Implementation Agreement Phase 1
•	MEF 23	Class of Service Implementation Agreement Part 1
•	MEF 24	Abstract Test Suite for UNI Type 2 Part 2: E-LMI

MEF 10 .<mark>1 repla</mark>ces and enhances MEF 10 Ethernet Services Definition Phase 1 and replaced MEF 1 and MEF 5. MEF 10.1.1 an amendment to MEF 10.1 has also been approved. MEF 6.1 replaced MEF 6.

This Presentation

• Purpose:

- This presentation is an introduction to MEF 20

Audience

- Equipment Manufacturers building devices that will carry Carrier Ethernet Services.
- Useful for Service Providers architecting their systems

Other Documents

- Presentations of the other specifications and an overview of all specifications is available on the MEF web site
- Other materials such as white papers and case studies are also available



Introducing MEF 20

The presentation covers

- MEF 20 Overview
 - Functionality and scope of MEF 20
- UNI definition and architecture
- Technical overview
 - MEF 20 technical details
 - Implementation options
- Key Questions
 - Relationship to other specifications and standards
 - Implementation Agreement structure
 - Comparison with legacy solutions
- Testing MEF 20 (using MEF 21 & MEF 24)
- Summary



MEF 20 UNI Type 2: Overview (In context of MEF 11)

MEF 11 introduced 3 types of UNI

– UNI Type 1 (now defined in MEF 13), November 2005

- Service Provider and Customer manually configure the UNI-N and UNI-C for services
- UNI Type 1.1 and 1.2 are defined
 - Type 1.1 : Non-multiplexed UNI for Services like EPL
 - Type 1.2 : Multiplexed UNI for Services like EVPL

UNI Type 2 (now defined in MEF 20)

- An automated implementation model allowing UNI-C to retrieve EVC status and configuration information from UNI-N
- Enhanced UNI attributes
- Additional fault management and protection functionality
- Backward compatibility with UNI Type 1

- UNI Type 3 (Possible future MEF Specification)

- Allows the UNI-C to request, signal and negotiate EVCs and its associated Service Attributes to the UNI-N. UNI
- Type 3 is for further study.

Functionality and Scope of MEF 20


- Ethernet Local Management Interface (E-LMI)
 - Allows UNI-C to retrieve EVC status and service attributes from UNI-N as specified in MEF 16
- Link OAM (Operation, Administration and Management)
 - Allows customer and service provider to monitor and diagnose the UNI connectivity via Link OAM (link level)
- Service OAM
 - Allows customer and service provider to monitor and diagnose the UNI connectivity via Service OAM (end-to-end)
- Protection
 - Capability to protect UNI against port failure via Link Aggregation protocol
- Enhanced UNI Attributes
 - Such as bandwidth profile per egress UNI, Maximum Transfer Unit size, etc. as defined in MEF 10., MEF 6.1
- L2CP Handling
 - Governs the passing or filtering of Layer 2 control protocols to the Ethernet Virtual Connections

Details of each mandatory and optional element are to be found in the specification



MEF 20 Enhances Carrier Ethernet Attributes

 Brings Carrier Ethernet to a new level by enabling new functionality to Carrier Ethernet attributes of scalability, service management, reliability, QoS and standardized services



MEF 20 Advances Carrier Ethernet Deployment

Carrier Ethernet growth challenges

- The success of Carrier Ethernet brings its own challenges, not the least of these is operational scalability
- Until now, MEF specifications have defined manual management process relying on manual or ad hoc processes. This cannot scale.

MEF 20

- Introduces automated processes for managing services, fault monitoring and management enabling at UNI level
 - Carrier Ethernet networks to scale
 - Carrier Ethernet networks to operate at reduce cost and
 - Creation of a framework for the dynamic service provisioning that will leverage the inherent benefits of MEF-defined Carrier Ethernet services



MEF Specifications Overview

MEF 20	User Network Interface (UNI) Type 2 Implementation Agreement	
Purpose	Specifies MEF UNI characteristics and operation in which customer side of the UNI is automatically configured by the network side of the UNI allowing verification of SLA and UNI connectivity. Additional objectives include support for Ethernet OAM (802.3ah, 802.1ag) over the UNI. Required for support of ELMI	
Audience	Equipment Manufacturers building devices that will carry Carrier Ethernet Services. Useful for Service Providers architecting their systems.	

Technical Committee Architecture Area

MEF 21/24	Abstract Test Suite for UNI Type 2, Phase 1: Link OAM	
Purpose	Provides the first of six possible test suites for UNI type 2 (MEF 20)	
Audience	Equipment Manufacturers building devices that will carry Carrier Ethernet Services. Useful for Service Providers architecting their systems.	
	Technical Committee Test and Messurement Area	

Technical Committee Test and Measurement Area





UNI Definitions

UNI Definitions

Background

- The User Network Interface in the MEF Specifications is an abstract concept. On one side of this point the service provider has responsibility and on the other, the customer.
- As such, it appears in diagrams in various positions in both in the MEF Specifications and in presentations
- This can be the source of confusion

Purpose and Audience

 For readers of the technical specifications and presentations, this short presentation provides clarity



Functionality and Scope of MEF 20

• Ethernet Local Management Interface (E-LMI)

 Allows UNI-C to retrieve EVC status and service attributes from UNI-N as specified in MEF 16

• Link OAM (Operation, Administration and Management)

Allows customer and service provider to monitor and diagnose the UNI connectivity via Link OAM (link level)

Service OAM

Allows customer and service provider to monitor and diagnose the UNI connectivity via Service OAM (end-to-end)

Protection

 Capability to protect UNI against port failure via Link Aggregation protocol


Enhanced UNI Attributes

 Such as bandwidth profile per egress UNI, Maximum Transfer Unit size, etc. as defined in MEF 10., MEF 6.1

L2CP Handling

 Governs the passing or filtering of Layer 2 control protocols to the Ethernet Virtual Connections

The MEF User Network Interface




CE: Customer Equipment, **UNI:** User Network Interface.



Functional Elements of the UNI (1)

- There are two functional elements (typically*) located in two connected devices situated on either side of the UNI demarcation point:
 - UNI-C: Executes the processes of the customer side
 - UNI-N: Executes the processes of the network side
 - * All the functions of the UNI-N and UNI-C need not be located in the same physical device as they may be located in several devices



CE: Customer Equipment, UNI: User Network Interface.




MEF certified Carrier Ethernet products

UNI-C and UNI-N Functional Elements (2)

Relationship between service frames (user generated), control and Carrier Ethernet management frames

- Subscriber to Subscriber service frames (including Subscriber's data, control and management frames) are handled by UNI-C and UNI-N data plane functional elements
- Control frames between Subscriber and Service Provider are handled by UNI-C and UNI-N control plane functional elements
- Management frames between Subscriber and Service Provider are handled by UNI-C and UNI-N management plane functional elements




How the UNI is shown in MEF Technical Specifications

Diagrams in the Specifications show the UNI in various positions. All three are valid but the first is by far the most likely to be seen in an operational network

- 1. At the port of the service provider equipment
 - (The usual position in the customer premises or multi-tenant location)


MEF

- 2. At the port of the customer's equipment
 - (Less typical although in theory the Service providers edge device need not be on the customer premises)



Carrier Ethernet Architecture

This slide shows the UNI in the context of other Carrier Ethernet architectural elements



UNIUser Network InterfaceNNINetwork to Network InterfaceUNI-CUNI-customer sideE-NNIExternal NNIUNI-NUNI-network sideI-NNIInternal NNI

The UNI is the physical demarcation point between the responsibility of the Service Provider and the responsibility of the Subscriber.





MEF 20 Technical Overview

MEF 20 in the context of MEF 13

MEF 13: UNI Type 1 Implementation Agreement

- Approved in November 2005
- UNI Type 1.1 and 1.2 are defined
- Type 1.1 : Non-multiplexed UNI for Services like EPL
- Type 1.2 : Multiplexed UNI for Services like EVPL
- S.P. and customer manually configure the UNI-N and UNI-C for services
- MEF 20 extends this ...



Technical Details (1)

Ethernet Local Management Interface (E-LMI)

 Allows UNI-C to retrieve EVC status and service attributes from UNI-N as specified in MEF 16

• Link OAM (Operation, Administration and Management)

- Allows customer and service provider to monitor and diagnose the UNI connectivity via Link OAM (link level)
- Link OAM monitors UNI's Physical Layer operation and health and improves fault isolation.
- Link OAM frames run between UNI-C and UNI-N.

Service OAM

- Allows customer and service provider to monitor and diagnose the UNI connectivity via Service OAM (end-to-end)
- A small but useful, set of capabilities based on ITU-T Y.1731 and IEEE 802.1ag
- Focused on fault management for the Maintenance Entity Groups crossing the UNI for all service types. A Maintenance Entity (ME) is a point-to-point relationship between two Maintenance Entity Points within a single Maintenance Entity Group

Technical Details (2)

Protection

Capability to protect UNI against port failure via Link
Aggregation protocol in various physical configurations

• Enhanced UNI attributes introduced with MEF 6.1 and MEF 10.1

- Bandwidth profile per UNI, per-EVC and per CoS ID egress bandwidth profiling of Committed Information Rate
- Maximum Transfer Unit size
- -Handling of E-Tree (rooted multipoint) services

L2CP Handling

- -Pass to EVC
- -Not pass to EVC (Filter)

MEF 20 Implementation Options

MEF 20 Specifies phased/alternate implementation. This allows quicker time to market and faster time to revenue for all concerned

UNI Type 2.1

Mandatory Features

- Backward comp. to UNI Type 1
- Service OAM
- Enhanced UNI attributes
- L2CP handling

Optional Features

- Link OAM
- Protection
- E-LMI

UNI Type 2.2

Mandatory Features

- Backward comp. to UNI Type 1
- Service OAM
- Enhanced UNI attributes
- L2CP handling
- Link OAM
- Protection
- E-LMI

Relationship to Other MEF and Industry Standards

Function	Source
MEF 20 Implementation Agreement is an enhancement to UNI Type 1	MEF13
Functionality includes capability for UNI-C to retrieve EVC status & configuration of service attributes from UNI-N via E-LMI	MEF16
Capability for customer and service provider to examine UNI connectivity via Link OAM	Clause 57 of IEEE 802.3
Capability for customer and service provider to examine UNI connectivity via Service OAM	ITU-T Y.1731 and IEEE 802.1ag
Capability to protect UNI against port failure via Link Aggregation	Clause 43 of IEEE 802.3

- Why has the MEF undertaken the initiative?
 - This exactly in line with the MEF's mission to undertake work that helps accelerate the adoption of Carrier Ethernet and to use other existing standards wherever practical
 - The MEF maintains standing liaisons with these industry standards bodies



Implementation Agreement Structure

- The Implementation Agreement
- Defines those elements that must be present and contains summaries of the concepts referred to in the previous slide
 - UNI Type 2 Discovery & Configuration ensures the elements to be managed are present
 - The remaining sections handle the features of 2.1 and 2.2 options
 - Where appropriate, these sections describe each function present in the referenced standards (e.g. Management Entity Groups) stating which are mandatory and optional

Comparison

 The addition of UNI type 2 functionality is comparable to baseline functionality of other legacy technologies


• However ...

 MEF 20 now enables the flexibility, service granularity and cost benefits of Carrier Ethernet not present in less flexible or lower bandwidth legacy solutions



Brief introduction to Abstract Test Suite for UNI Type 2 (MEF 21 & MEF 24)

MEF 21/MEF 24: Testing UNI Type 2



- Further Test projects are in preparation
- E-NNI will leverage MEF 21 test cases
- MEF Certification will be decided in due course
- E-NNI will leverage MEF 21 test cases
- MEF Certification will be decided in due course

MEF 21 Part 1 Scope

- Covers test procedures for Link OAM described in the UNI Type 2 IA & clause 57 of IEEE 802.3-2005
 - An overview of the different groups of requirements that compose Link OAM is provided as follows:
 - OAM Discovery process initiation and DTE reactions
 - Information OAMPDU exchange
 - Event Notification OAMPDU exchange
 - Variable Request & Response OAMPDU exchange
 - Loopback Control OAMPDU exchange and DTE reactions
 - Organization Specific OAMPDU exchange

Structure

- Test Configurations for UNI-C and UNI_N
- 140 Test Procedures for Link OAM



MEF 24 Part 2 Scope

- Covers test procedures based on a combination of requirements for E-LMI described in MEF 20 User Network Interface (UNI) Type 2 Implementation Agreement and in MEF 16 Ethernet Local Management Interface.
 - An overview of the different groups of requirements that compose E-LMI is provided as follows:
 - E-LMI Framing Mechanisms
 - E-LMI Messages
 - E-LMI Procedures
 - E-LMI Impairments

Structure

- Test Configurations for UNI-C and E-LMI
- 140 Test Procedures for UNI-N and E-LMI

Final Word

- Next Actions
 - Read the detailed MEF 20 Implementation Agreement
 - Review MEF 21 and MEF 24 Abstract Test Suites available on the MEF web site





Accelerating Worldwide Adoption of Carrier-class Ethernet Networks and Services

www.MetroEthernetForum.org